1. An array display comprising:

a plurality of panels abutted together in side-by-side arrangement to form an array and defining seams between adjacent panels; and

a resilient material around the panels, the resilient material of adjacent panels abutting to form the seam.

2. The display of claim 1 wherein said resilient material is a foam.

3. The display of claim 1 wherein said resilient material is a polymer.

4. The display of claim 1 wherein said resilient material is black.

5. The display of claim 1 including optical integrator plates positioned over said panels, a filler material positioned between said plates.

6. The display of claim 5 wherein said filler material matches the optical characteristics of said optical integrator plates.

7. The display of claim 5 wherein said resilient material is positioned beneath said filler material, said resilient material including an upper portion, said integrator plates including black matrix lines, said upper portion arranged to substantially match the optical characteristics of said black matrix lines.

8. The display of claim 7 wherein said upper portion is positioned between said optical integrator plates and said panels.

9. The display of claim 1 including black matrix lines formed on the upper surface of said panels, said material including an upper portion that substantially matches the appearance of said black matrix lines.

10. The display of claim 9 wherein said upper portion is made of a material that is different from said resilient material.

11. A method comprising:

abutting a plurality of panels together in side-by-side arrangement to form an array display;

defining seams between adjacent panels;

locating a resilient material around the periphery of each panel; and

abutting the resilient material of adjacent panels to form a seam.

12. The method of claim 11 including forming the seam of a resilient foam material.

13. The method of claim 11 including forming the seam of resilient silicone material.

14. The method of claim 11 including using a black material to form said seam.

15. The method of claim 11 including positioning optical integrator plates over said panels and filling the region between said optical integrator plates and said panels with a filler material.

16. The method of claim 15 including matching the optical characteristics of said optical integrator plate with said filler material.

17. The method of claim 15 including providing a first seam material between said optical integrator plates, said first seam material being substantially transparent and matching the optical characteristics of said optical integrator plates.